

# PREMIUM CAST IRON SEWAGE PUMP

## APPLICATIONS

Ideal for high volume sewage, effluent, and general wastewater applications in places like parking lots, leaching fields, and laundry facilities.

## FEATURES & BENEFITS

- Automatic submersible cast iron sewage pump
- PSC dual bearing motor with overload protection
- Capable of passing up to 2" diameter semi-solids
- Piggyback tethered float switch



Model	Item Number	UPC	HP	Volts	Amps	Discharge	Cord Length	Gallons Per Hour at Height						Shut-Off	On/Off Levels	Min. Basin Diameter
								0'	5'	10'	15'	20'	25'			
RL52WAM	620051	0 10121 13855 1	1/2	115	11.4	2" FNPT	20'	9000	7200	6000	4500	960	-	22'	On: 16" -18" Off: 9" -11"	18" or more
RL75WAM	14942635	0 10121 14583 2	3/4	115	10.3	2" FNPT	10'	10500	9300	7620	5880	4200	1740	28'	On: 17.5" Off: 10.5"	18" or more

## Carton Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL52WAM	11"	13.5"	16"	50	1.38	27	9	3
RL75WAM	11.75"	13.75"	15.5"	57	1.45	27	9	3

Premium Cast Iron Sewage Pump

