

ALUMINUM UTILITY PUMPS

APPLICATIONS

Ideal for general water transfer applications and household water removal in places like basements, crawl spaces, rooftops, and window wells.

FEATURES & BENEFITS

- Submersible 115 Volt utility pumps
- Corrosion-resistant aluminum casing for superior heat dissipation
- Lightweight portability
- Removes water to within 1/4" of surface
- 3/4" garden hose adapter included
- Oil-free motor design



RL-160U

RL-250U

Model	Item Number	UPC	HP	Amps	Volts	Discharge	Intake	Cord Length	Gallons Per Hour at Height					Shut-Off
									0'	5'	10'	15'	20'	
RL-160U	620109	0 10121 12595 7	1/6	2.1	115	1" FNPT 3/4" GHT	Screened Bottom	10'	1300	1200	840	420	-	19'
RL-250U	14942734	0 10121 14157 5	1/4	3.2	115	1" FNPT 3/4" GHT	Screened Bottom	10'	1500	1440	1140	720	180	21'

Carton Specifications

Master Pack Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Master Pack Qty.
RL-160U	6"	6"	12"	9	0.25	6
RL-250U	6"	6"	12"	9.5	0.25	6

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL-160U	18.75"	12.75"	13"	54	1.80	21 Master Packs	7 Master Packs	3
RL-250U	18.75"	12.75"	13"	57	1.80	21 Master Packs	7 Master Packs	3

Aluminum Utility Pumps

