

# ALUMINUM SEMI TRASH PUMPS



## APPLICATIONS

Ideal for high volume transfer and dewatering. Can handle liquid slurries including sand, pebbles, and suspended solids less than 1/2" in diameter.

## FEATURES & BENEFITS

- Durable cast iron semi-open style impeller
- Lightweight aluminum outer casing: includes heavy-duty roll frame
- Wear resistant silicon carbide mechanical seal
- Self-priming to 25' of suction lift
- Built-in check valve
- EPA certified



6RLAG-3ST



6RLAG-2ST



Model	Item Number	UPC	cc	Intake	Discharge	Suction Lift	Max Head	Max Flow GPM	Fuel Tank (qt)	Engine
6RLAG-2ST	617052	0 10121 13750 9	208cc	2" MNPT	2" MNPT	25'	92	150	3.8	4 Stroke OHV (208cc)
6RLAG-3ST	617054	0 10121 13752 3	208cc	3" MNPT	3" MNPT	25'	85	264	3.8	4 Stroke OHV (208cc)

## Carton Specifications

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
6RLAG-2ST	15.25"	19"	16.5"	52	2.77	12	6	2
6RLAG-3ST	15.25"	19"	16.5"	66	2.77	12	6	2

## Aluminum Semi Trash Pumps

