



## PRE-CHARGED PRESSURE TANKS

### APPLICATIONS

For maintaining the water pressure in a residential water pump system when the pump is not running.

### FEATURES & BENEFITS

- **ANSI/NSF Standard 61 approved**  
Assures safe, clean drinking water
- **Blended butyl rubber diaphragm system**  
Isolates the air charge from the water chamber and provides long tank life
- **Heavy-duty steel construction**  
16 gauge cold rolled steel with appliance-quality paint
- **Steel clench ring protects diaphragm from rubbing against tank wall**  
Eliminates abrasion and reduces condensation
- **Brass air valve with O-ring seal**  
Allows adjustment of air pre-charge



Model	Item Number	UPC	Gallons	Drawdown @ 30/50 PSI (gal)	Fixtures	Type	System Connect
RL2	604452	0 10121 12335 9	2.1	0.7	-	Inline	3/4" MNPT
RL4	604453	0 10121 12336 6	4.8	1.5	-	Inline	3/4" MNPT
RL8	604454	0 10121 12337 3	8.5	2.6	-	Inline	3/4" MNPT
RL6H	604529	0 10121 12126 3	5.3	1.6	1	Horizontal	3/4" MNPT
RL14H	604493	0 10121 12124 9	14	4.3	4	Horizontal	3/4" MNPT
RL14	604456	0 10121 12338 0	14	4.8	4	Vertical	1" NPT
RL20	604457	0 10121 12339 7	20	6.8	6	Vertical	1" NPT
RL33	604449	0 10121 12334 2	33	11.3	11	Vertical	1" NPT
RL44	604459	0 10121 12341 0	44	15	14	Vertical	1-1/4" NPT
RL81	604541	0 10121 12365 6	81	27.6	27	Vertical	1-1/4" NPT
RL119	604531	0 10121 12360 1	119	40.6	39	Vertical	1-1/4" NPT

### Carton Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL2	8.33"	8.33"	12.75"	5	.51	60	20	3
RL4	11.12"	11.12"	15"	10	1.07	36	12	3
RL8	13.5"	19.5"	13.5"	15.4	2.06	18	6	3
RL6H	10.5"	18"	12.25"	13.3	1.34	18	6	3
RL14H	15.75"	21.25"	17.25"	27	3.34	8	4	2
RL14	16.5"	16.5"	23"	29	3.62	8	4	2
RL20	16.75"	16.75"	30"	35	4.87	4	4	1
RL33	16.3"	16.3"	44"	55	6.77	4	4	1
RL44	21.3"	21.3"	38.25"	66	10.04	2	2	1
RL81	21.5"	21.5"	60"	101	16.05	2	2	1
RL119	26.75"	26.75"	61.5"	160	25.47	1	1	1

