

PRE-CHARGED PRESSURE TANKS

APPLICATIONS

For maintaining the water pressure in a residential water pump system when the pump is not running.

FEATURES & BENEFITS

- **ANSI/NSF Standard 61 approved**
Assures safe, clean drinking water
- **Blended butyl rubber diaphragm system**
Isolates the air charge from the water chamber, re-enforced in specific wear areas for longer life
- **Heavy-duty steel construction**
18 gauge cold-rolled steel
- **Leak-resistant, O-ring sealed air valve cap**
Allows adjustment of air pre-charge
- **Unique dual water/air seal**
Patented design offers superior leak protection
- **Durable two-part paint finish suitable for outdoor use**
Provides hundreds of hours of UV and salt spray protection*



Inline




Horizontal



Vertical



Model	Item Number	UPC	Gallons	Drawdown @ 30/50 psi (gal)	Fixtures	Type	System Connect
RL2	604452	0 10121 12335 9	2.1	0.7	-	Inline	3/4" MNPT
RL4	604453	0 10121 12336 6	4.8	1.5	-	Inline	3/4" MNPT
RL8	604454	0 10121 12337 3	8.5	2.6	-	Inline	3/4" MNPT
RL6H	604529	0 10121 12126 3	5.3	1.6	1	Horizontal	3/4" MNPT
RL14H	604493	0 10121 12124 9	14.0	4.3	4	Horizontal	3/4" MNPT
RL16*	604587	0 10121 15197 0	15.9	4.9	5	Vertical	1" NPT
RL20H*	604581	0 10121 15158 1	21.1	6.2	7	Horizontal	1" NPT
RL21*	604582	0 10121 15159 8	21.1	6.5	7	Vertical	1" NPT
RL34*	604583	0 10121 15160 4	34.3	10.6	11	Vertical	1" NPT
RL40*	604584	0 10121 15161 1	40.0	12.4	13	Vertical	1" NPT
RL81	604541	0 10121 12365 6	81.0	27.6	27	Vertical	1-1/4" NPT
RL119	604531	0 10121 12360 1	119.0	40.6	39	Vertical	1-1/4" NPT



Carton Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL2	8.33"	8.33"	12.75"	5.0	0.51	60	20	3
RL4	11.12"	11.12"	15"	10.0	1.07	36	12	3
RL8	13.5"	19.5"	13.5"	15.4	2.06	18	6	3
RL6H	10.5"	18"	12.25"	13.3	1.34	18	6	3
RL14H	15.75"	21.25"	17.25"	27.0	3.34	8	4	2
RL16	15.5"	15.75"	25.13"	24.9	3.55	6	6	1
RL20H	15.75"	29"	17.25"	35.8	4.56	6	3	2
RL21	15.75"	15.5"	32.75"	35.8	4.63	6	6	1
RL34	17.25"	17.5"	43.25"	58.8	7.56	4	4	1
RL40	21.5"	21.25"	37.25"	76.3	9.85	2	2	1
RL81	21.5"	21.5"	60"	101.0	16.05	2	2	1
RL119	26.75"	26.75"	61.5"	160.0	25.47	1	1	1

