

HEAVY-DUTY SEWAGE PUMPS

APPLICATIONS

Ideal for high volume raw sewage removal applications.

FEATURES & BENEFITS

- Automatic submersible cast iron sewage pump ideal for high volume sewage and effluent needs
- Clog-resistant design capable of passing 2" diameter solids
- Heavy-duty cast iron construction for years of service and reliability
- Tethered float switch for reliability in automatic operation in basins 18" diameter or greater
- Energy-efficient PSC motor



Model	Item No.	UPC	HP	Volts	Amps	Discharge	Cord Length	Gallons Per Hour at Height						Shut-off	On/Off Levels	Min. Basin Diameter
								0'	5'	10'	15'	20'	25'			
RL50WA	14942663	0 10121 00060 5	1/2	115	9.3	2" FNPT	20'	7200	6000	4800	3180	1200	-	22'	On: 16"-18" Off: 9"-11"	18" or more
RL75WA	14942664	0 10121 00061 2	3/4	115	11	2" FNPT	20'	8400	7800	6600	5400	4200	2400	28'	On: 17"-20" Off: 10"-12"	18" or more

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL50WA	10.2"	11.6"	17.4"	42.8	1.38	27	9	3
RL75WA	10.2"	11.6"	17.8"	44	1.2148	24	12	2

